

GoDEX AG2000-ZX Print-and-Apply System



plant pot print-and-apply

The GoDEX AG2000-ZXP system has been specifically designed to label tapered round or square plant pots.

Labels are printed at 200, 300 or 600dpi resolution using a GoDEX ZX1000i series industrial label printer and applied with an extended smoothing brush.

Tilt adjustment allows quick changeover between different pot sizes and shapes.

Systems can be supplied to work on an existing conveyor or with an integrated conveyor customised to suit the products being labelled.



scan to see video



GoDEX



versatile design

AG2000-ZXP systems can be installed to label pots on an existing conveyor using a floor stand with adjustable tilt mechanism for the applicator to cater for different pot sizes and shapes.

Alternatively, an integrated conveyor can be included, custom designed to suit the products to be labelled and surrounding equipment. A wide choice of driven belt and modular conveyors is available with stainless steel, aluminium or powder-coated finish.

features and options

Powerful GoLabel software, GoAPP Android app, Windows and MacOS drivers are included with all AG2000-ZXP systems.

Ethernet, USB and serial interfaces are included as standard with optional WiFi and Bluetooth.

Stand-alone operation is possible allowing the system to be operated without a PC or host system connected. The printer touchscreen can be used to select label designs and enter variable data.

Inline barcode readers and vision systems allow all products to be quality checked and automatically rejected.



Specification

AG2000-ZXP

Printer:	GoDEX ZX1200i, ZX1300i or ZX1600i
Print method:	Thermal transfer or direct thermal
Print resolution:	200, 300 or 600dpi
Label size:	Width 25 to 110mm / length 30 to 150mm
Application speed:	Up to 24m/min (400mm/sec) - independent of print speed to ensure optimum print quality
Label and ribbon roll sizes:	Label rolls up to 200mm diameter / ribbons up to 450m length
Dimensions LxWxH:	965 x 400 x 270mm including printer
Weight:	7Kg excluding printer / 20.6Kg including printer (excluding floor stand)
Standard interfaces:	Ethernet, USB and serial
Optional interfaces:	WiFi, Bluetooth and parallel
Warranty:	Applicator 3 years / printer 5 years (excluding wear parts)
Options:	Floor stands, custom integrated conveyors, stand-alone kit, status beacon, inline barcode reader or vision system with reject station, various software and integration options, WiFi and Bluetooth interfaces.